

Electronic Point Of Sale Touch POS NOVO Series

NOVO - 2600



HIGHLIGHTS

- Full aluminum housing
- True flat water proof touch screen
- Various options of peripherals
- Ultra-thin fashion design
- Easy Operation

OPTIONAL

- Capacitive multi-points touch panel
- VFD customer display
- Magnetic card reader
- 9.7" second display

Your Reliable POS Partner



NOVO-2600

Electronic Point Of Sale Touch POS NOVO Series



Optional MSR



Optional 9.7" display



Various interface



VFD customer display



Slim design

SPECIFICATIONS

Motherboard	J1900
CPU	Intel® Bay Trail-D Celeron Quad Core 2.0GHz
Chipset	
Memory	1 x DDR3 4GB
HDD	2.5" 500GB (SSD:MSARA 128/256 GB optional)
Network	RTL8111E for 1000Mbps
Touch Screen	5-wire resistive 35,000,000 times touch life (Capacitive multi-points touch screen optional)
LED	15" TFT LED
Max Resolution	1024 x 768
Brightness	250 nits
Response Time	5ms
I/O Ports	2*COM ports 1*LPT port 1*VGA port 1*LAN port 4*USB 2.0 ports 1*DC port 2*Audio: Mic in, Line out
Power supply	DC12V, 7A
Environment	Operating temperature and humidity:-10℃ to 40 ℃,20-80% RH Storage temperature and humidity:-20℃ to 60℃,20-90% RH
EMC&Safety	CE,FCC,RoHS,CB,CCC
Dimension	430*420*270mm
Gross weight	5.2kg

Dealer

